

# Galaxy Colour Chem

Industrial Chemical Trading

Rajkot, Gujarat | Est. 2001 | Commissioner & PESO Licensed

GST: 24AHEPK9990Q1ZF | +91 97253 88415 | galaxycolorchem@gmail.com

PRODUCT DATASHEET

## Toluene

C<sub>7</sub>H<sub>8</sub> | CAS 108-88-3

### Specification Table

Test Description	Min	Max	Unit	Test Method
Saybolt Color	+30	—	—	ASTM D 156
Density at 15°C	0.847	—	Kg/dm <sup>3</sup>	ASTM D 4052
Distillation IBP	110	—	Deg.C	ASTM D 850
Distillation 50%	110.6	—	Deg.C	ASTM D 850
Distillation DP	111.80	—	Deg.C	ASTM D 850
Flash Point	7	—	Deg.C	ASTM D 56
Copper Corrosion (3h@50°C)	—	1a	—	ASTM D 130
Sulphur Content	Free	—	ppm/wt	ASTM D 853
Aromatics	99	—	Vol.%	ASTM D 1319

Note: Physical properties are not monitored constantly. Values represent standard specification limits.

### Applications

<b>Paints &amp; Coatings</b> Solvent in paints, lacquers, varnishes, and industrial coatings.	<b>Adhesives &amp; Sealants</b> Key solvent in rubber-based adhesives, contact cements, and sealants.
<b>Printing Inks</b> Primary carrier solvent in gravure and flexographic printing inks.	<b>Chemical Synthesis</b> Feedstock for benzene, xylene, benzoic acid production.
<b>Pharmaceuticals</b> Solvent and reagent in drug synthesis and laboratory processes.	<b>Rubber &amp; Polymers</b> Solvent for natural rubber, neoprene, and polystyrene.
<b>Cleaning &amp; Degreasers</b> Degreasing agent for metals, equipment, and industrial surfaces.	<b>Leather Processing</b> Applied in leather finishing and coating formulations.